

## QAT - CS - 006 -V01 - CM#0 - 121118

Security Information:

N - M#0 - E -E - C - N - X -X - YN

Document name: Material safety data sheet

60% Quality rubber bands

1. Identification of the substance and company

KOH-I-NOOR ITALIA Spa - Via dell'Artigianato, 1/3 -Company indentification

20082 Binasco (Milano) - Italy

Tel: (+39) 02 9001151 Fax: (+39) 02 90011523

Product name Rubber band

Formula name 60% Quality Rubber Bands

MSDS information Issue by Mr. Narin Intharathong (Quality Assurance Manager)

2. Hazard identification

Eye contact

Emergency overview This product is not hazardous as defined by US OSHA, Canadian

WHMIS, the US Consumer Products Safety Commission or the .

No MSDS is required for this product.

Not skin irritation on prolonged contact.

This products has low oral acute toxicity.

Direct eye contact may cause mild irritation.

In using this product it is prudent to avoid eye contact.

Can prolonged direct contact with skin and clothing.

Symptoms of overexposure N/A

Inhalation The inhalation not cause irritation of nose, throat.

Skin contact

Ingestion Swallowing may cause gastrointestinal irritation.

This product not for eat.

Chronic effects Not have.

Medical conditions Not have specify for this product.



## QAT - CS - 006 -V01 - CM#0 - 121118

Security Information:

N - M#0 - E -E - C - N - X -X - YN

**Document name:** Material safety data sheet

3. Composition/information on in	gredients
Composition	phr
Natural rubber	100
Chemical additive	TE 1175 (ES (ES (ES (ES (ES (ES (ES (ES (
<b>Note:</b> (Phr) refer to: Parts per Hundred what amount of certain ingredien	Rubber, a measure used by rubber chemists to depict ts are needed.
4. First aid measures	
Ingestion (Swallowed)	Do induce vomiting and. Give one to two eight-ounce glasses of water to gargle if the patient of conscious and responsive.  Never give anything by mount to an unconscious person and hurry up to see the doctor for medical service.
Eye contact	Flush eyes with plenty of water, lifting upper and lower eyelids occasionally. Get medical attention persists.
Skin contact	First aid would not generally be required for this matter. Sensitive individials if has mild irritation do rinse off with water.
Inhalation (Breathing)	First aid would not generally be required for this matter. If irritation is experienced, remove to fresh air. Get medical attention if irritation persists.
5. Fire-fighting measures	
Extinguishing media	Water, all purpose (ANC) dry chemical, CO <sub>2</sub> , foam.
Special intervention method	During emergency conditions, overexposure to thermal decomposition products may cause a health hazard.  And approved, self-contained breathing apparatus should be worn.
Special exposure hazards	Easily ignited. However, when ignited, and particularly in bulk storage, a hot and difficult to control fire may develop. This product emits acrid smoke and fumes when burning.



### OAT - CS - 006 - V01 - CM#0 - 121118

Security Information:

N - M#0 - E -E - C - N - X -X - YN

**Document name:** Material safety data sheet

6. Accidental release measures

The action after.

Wear personal protective equipment. Sweep or vacuum up, avoid generating airborne dust. Place in closed container for recycle or disposal.

7. Handling and storage

Precautions

Keep away from excessive heat and open flame.

Handling

Avoid eye contact.

Storage

Store in a cool dry, the storage temperature should be 25-32 °C and products should be stored away from direct sources of heat such as direct sunlight, boilers, radiators etc. The relative humidity must be such that, given the variations of temperature in storage, condensation does not take place. In any event, the relative humidity of the atmosphere in storage should be less than 70 %. Should be protected from light sources, in particular direct sunlight or intense artificial light having a high UV rays content. In order to avoid damage to the stored rubber products, precautions has to be taken to protect these products from all sources of ionizing radiation. As ozone is particularly harmful to rubber, storage rooms should not contain any equipment that is capable of generating ozone, such as mercury vapour lamps or high -voltage electrical equipment giving rise to electric sparksor silent electrical dischargs. The storage rooms must be excluded from Combustion gases and organic vapours, as they may give rise to ozone via photochemical processes. Rubber should be stored free from super imposed tensions and compressive stresses or other cause of deformations. Where products are packed in a strain-free condition, they should be stored in their original packaging. Should not be allowed to come into contact with liquid or semi-liquid materials (for example, petrol, greases, acids, cleaning fluids) or their vapours at any time during storage. Should not be stored in contact with such metals (in particular, copper and manganese) except when bonded to them but should be protected by wrapping in or by separation with a layer of suitable material, e.g. polyethylene or paper.



# QAT - CS - 006 -V01 - CM#0 - 121118

Security Information:

N - M#0 - E -E - C - N - X -X - YN

**Document name:** Material safety data sheet

8. Exposure controls / personal prote	ction
Ventilation protection	When this product is heated, provide enough fresh air/or exhaust to remove the hot processing vapors from the work area.
Respiratory protection	Under normal conditions of use, respiratory protection should not be required.
Skin protection	Who have prolonged contact with this product should practice good personal hygiene by frequent washing of hands and arms with soap and water.
Eye and hand protection (Under high tension condition using)	Safety glasses and leather gloves while under high tension using.
9. Physical and chemical properties.	<u> </u>
Specific gravity (g/cm³)	1.29-1.39
Tensile strength (Mpa)	16-20
Elongation at break (%)	585-715
Tension set (%)	< 6
10. Stability and reactivity	# # # # # # #
Reaction of ozone (O <sub>3</sub> )	The reaction of ozone with an unsaturated elastomer is very rapid until the double bonds at the surface have reacted. The degree of reaction increasing follow the stress and strain. Effected to cracking of surface.
11. Toxicology information	
Using experience	Long team experience of this product type indicates no danger to health when properly handled under normal condition.
12. Ecological information	<del>(3) (3) (3) (3) (3) (3)</del>
Bioaccumulation	No evidence for bioaccumulation.
Ecotoxic effects	The product is not classified as dangerous for the environment
0	Quality assurance department MHK



### QAT - CS - 006 - V01 - CM#0 - 121118

Security Information:

N - M#0 - E -E - C - N - X -X - YN

**Document name:** Material safety data sheet

13. Disposal considerations	<u> </u>	123 BB BB B	3
Waste	Waste product she waterways withou	ould not be discharged directly into d t tretment.	rains or
Disposal	Disposal of product and packaging should be treated in a separation and biological treatment plant.		a
14. Transport information	<b>R R</b>	)	
Transport	This product is no	classified as dangerous for carriage.	
Transport  15. Regulatory information	This product is no	classified as dangerous for carriage.	
(ES (ES (ES (ES	This product is no	<u> </u>	
15. Regulatory information  N. 886-2559 Regulations (CFR) 21, Section 177.2600	<u> </u>	classified as dangerous for carriage.  N/A N/A	
15. Regulatory information  N. 886-2559  Regulations (CFR) 21, Section 177.2600  Reach Conformity to 1907/2006/EC	<u> </u>	N/A	
15. Regulatory information  N. 886-2559 Regulations (CFR) 21, Section 177.2600 Reach Conformity to 1907/2006/EC ROHS Conformity to 2011/65/EU	<u> </u>	-N/A N/A	
15. Regulatory information  N. 886-2559 Regulations (CFR) 21, Section 177.2600 Reach Conformity to 1907/2006/EC ROHS Conformity to 2011/65/EU Safe for use in food or food packaging a	according to U.S.	N/A N/A N/A	
15. Regulatory information  N. 886-2559 Regulations (CFR) 21, Section 177.2600 Reach Conformity to 1907/2006/EC ROHS Conformity to 2011/65/EU	according to U.S. ode of Federal	N/A N/A N/A N/A	

#### 16. Other information

This information given is based on our knowledge of this product, at the time of publication. Is is given in good faith. The attention of the user is guide to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse of the user from knowing and applying all the regulations governinghis activity. It is the sole reponsibility of the user take all precautions required in handing the product. The aim of the mandatory regulationsmentioned is to help the user to fulfil his obligations regarding the use of hazardous. This information is not exhaustive. This does not exonerate the user from ensuring that legal obligation, other that those mentioned, relating to the use and storage of the product, do not exist. This is solely his reponsibility, we do not assume resposibility and expressly disclaim liability for loss, damage or expense arising out of any way. If the product is used as a component in another product, this MSDS information may not be applicable.



Spettabile
OFFICE DISTRIBUTION S.p.A.
Via Cassino D'Alberi ,21
20067 Tribiano (MI)

Binasco, 22 luglio 2020

Oggetto: DICHIARAZIONE DI ORIGINE

Dichiariamo con la presente che gli elastici a marchio MARKIN da noi distribuiti, sono di origine tailandese.

Cordiali saluti

Giuseppe Massetti Amministratore delegato