

Profilo paracolpi per spigoli E8R

Codice articolo	1126130	Minimo d'ordine	5 Pezzo
Colore	Giallo / nero	EAN minimo d'ordine	4005546735870
Confezionamento	Conf. da 5 pezzi	Peso confezione (lordo)	1876 G
EAN	4005546735863	Paese d'origine	CN



Descrizione prodotto

- Profilo di protezione adesivo per spigoli in schiuma poliuretanica flessibile
- Per uso interno
- Può essere applicato su scaffali, sporgenze, travi a T in aree di produzione, reparti spedizioni e magazzini, scantinati, trombe delle scale e garage
- Adatto per segnalare punti pericolosi, prevenire infortuni dovuti a urti e danni ai veicoli e carrelli di stoccaggio
- I profili possono essere tagliati alla lunghezza desiderata con un taglierino affilato
- Colore conforme alla norma ASR A1.3, simile a RAL 1003/9004 (giallo segnale / nero segnale)
- Classe di incendio conforme alla norma DIN EN 13501-1:2018-12 classe E
- Resistente alla temperatura da -30°C a +70°C
- Lunghezza profilo: 1 m
- Larghezza fessura interna: 8 mm

Caratteristiche prodotto

Profondità esterna (mm)	40
Altezza esterna (mm)	40
Larghezza esterna	1,000 mm
Marchio	DURABLE
Larghezza interna (mm)	8

1126130_PDS_DURABLE_it_IT.pdf | 2025-01-12 01:17

1/2

DURABLE Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77 - 79 · 58636 Iserlohn · Germany
Phone +49 (0) 2371 662 0 · Fax +49 (0) 2371 662 221
Mail durable@ durable.de | durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.



Profilo paracolpi per spigoli E8R

Altezza interna (mm)	20
Tipologia di adesivo	Permanente
Spessore materiale	17 mm
Colori speciali	Simile a giallo segnale RAL 1003 / nero segnale RAL 9004